

Hardware / Integrated Folding Doors / Screens / Shades

Presenting a great upgrade opportunity for homeowners looking to replace their current sliding door system.

Our new bottom sill/track system combined with the proven F3 Floor-rolling systems, robust TwinPoint Gen2 Lockset and the door panels allows the traditional sliding door to be removed and new bi-folding (2) doors installed to 'double your doorway'.

Doubling your doorway improves your access and connection with the outdoor living area. It more than doubles the airflow to reduce reliance on air-conditioning and provides fresh healthy air.

- Can be installed with our award winning S2 Insect Screen. Finger-tip control makes opening and closing child's play. Fully retracts when not in use.
- Frame is provided fully machined and finished ready for the panels to be installed
- Slimline head and sill profiles work with F3 Floorrolling hardware to remove overhead vertical load. The frame can be simply installed on existing building structures, even with limited header size.
- TwinPoint Gen2 Lock is a stylish alternative to surface mounted dropbolts. Simple to install and use, its elegant central handle operates concealed top and bottom bolts, closing doors in one easy movement.
- Optional double handles, with an outside key and interior thumbturn, provides convenient and secure exterior access.



Double your doorway


Horizontal section


Frame width	71"	71 1/4"	71 1/2"	71 3/4"	72"
Panel width	33.847"	33.972"	34.097"	34.222"	34.347"
	33 13/16"	33 15/16"	34 1/16"	34 3/16"	34 5/16"


Panel width formulas


2 panels: (Frame width - 3.306") / 2














Vertical section



Frame height	79"	79 1/4"	79 1/2"	79 3/4"	80"
Panel height	75.938"	76.189"	76.439"	76.689"	76.939"
	75 15/16"	76 3/16"	76 7/16"	76 11/16"	76 15/16"


Panel height formula

All panels: Frame height - 3.062"





Profiles




Sill Thermally broken aluminum


Removeable sill cover Aluminum



Profiles with S2 screen




Sill with S2 on Shim on Exising Flooring



Profiles with S2 screen




Jamb






Hardware for 2 left panels



Hardware for 2 right panels






End carrier setStraight hinge setTwinPoint Gen2Pivot setLeftLeftRight







Frame machining details



